



Eco-Smart, Inc.
4411 Bee Ridge Rd. #344
Sarasota, FL 34233
888-329-2705
www.ecosmartinc.com

Ship to:

Phone:

Email:

Date:

Fabric Panel Field Measuring Form

Window # / Name	Span Dimension	Non-Span Dimension	Panel Qty	Notes - Panel Type: FS (Direct or Pull Down) or AG, Considerations, Substrate Type: Wood, Filled Concrete, Hollow Concrete
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
21				
22				
23				
24				
25				
26				
27				
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				
39				
40				

Limitations: Fabric Shield: Span min = 9", Span max = 108"; Non-Span min = 12", Non-Span max = 144".

Astroguard: Span Max: 18', Non-Span Max - Unlimited (limit is unweildiness)

Span and Overlap Notes: Span Dimension is Grommet to Grommet Distance. Non-Span is edge to edge without grommets.

Minumum Required Overlap:

Concrete Block: 2.5" overlap on span, 1" on non-span. Wood Frame: 0.75" to 1" overlap on all sides.

Reminder on corners: Grommets are 1" from edge at corner - don't place corner grommet too close to an obstruction.

Questions: Call 941-376-8484