



Eco-Smart, Inc.  
 4411 Bee Ridge Rd. #344  
 Sarasota, FL 34233  
 888-329-2705  
 www.ecosmartinc.com

Ship to: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 Phone: \_\_\_\_\_  
 Email: \_\_\_\_\_

**Fabric Panel Field Measuring Form**

Date: \_\_\_\_\_

Opening Name	Panel Qty	Span Opening	Span Overlap (Total to the 1/2")	Non-Span Opening	Non-Span Overlap (Total to the 1")	Notes - Panel Type: FS (Direct or Pull Down) or AG, Considerations, Substrate Type: Wood, Filled Concrete, Hollow Concrete
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						
21						
22						
23						
24						
25						

**Limitations:** Fabric Shield: Span min = 9", Span max = 108"; Non-Span min = 12", Non-Span max = 144".  
 Astrogard: Span Max: 18', Non-Span Max - Unlimited (limit is unweildiness)  
**Span and Overlap Notes:** Span Dimension is Grommet to Grommet Distance. Non-Span is edge to edge without grommets.  
**Mininum Required Overlap:**  
 Concrete Block: 2.5" overlap on span, 1" on non-span. Wood Frame: 0.75" to 1" overlap on all sides.  
**Reminder on corners:** Grommets are 1" from edge at corner - don't place corner grommet too close to an obstruction.  
**Questions: Call 941-376-8484**