

Induction Lighting: 40W Self Ballasted (E27/E40 Base)

Induction Lamp (40W)

V Series:

Compact ballast design, low wattage (40w)
International standard Edison lamp base.
AC: 120V、220V、277V、



1. Special mushroom shape structure, luminous points focus, uniform light emission in 360 degree space.
2. Bigger light surface area than other lamps with the same wattage, soft light.
3. Compact integrated structure, match for all kinds of small size lighting fixtures, and perform lighting effects of different spatial place.
4. Spiral lamp base, easily to retrofit all kinds of compact lamps.
5. Special magnetic hoop structure, effectively avoid magnetic leakage and magnetic core power loss, perfect heat dissipation ability.
6. Special ferrite magnetic core, maintain the magnetic core inductance stable in wide temperature range; unique B-H curve, reduce the magnetic hysteresis loss and magnetic core loss.
7. Amalgam inside, less pollution, eco-friendly.
8. Special amalgam, well suited for the instant-start features and stability characteristics in the wide range of temperature.
9. With special technology, power start faster, better stability.
10. Self-developed inert gas formula, ensure the consistency of light efficiency and power.
11. Full range of color temperature, a variety of power options
12. Inside compact electronic ballast, unique ballast technology, improve the power factor.
13. Special winding technology, improve the low temperature start ability.
14. We can produce variety of wattage upon the customers' special requirement.

Specifications of LVD Induction Lamp

| Series | Type | Warr. (Year) | Volts(V) | Rated luminous flux(Lm) | Pupil luminous flux (Plm) | Lamp specification(mm) | Wattage(W) |
|--------|------|--------------|------------------|-------------------------|---------------------------|------------------------|------------|
| V | V-40 | 5 | 220/120/ | 2600 | 3900~4600 | 115x88x241 (E27) | 40 |
| | | | 277/347 12/24 | | | 115x88x261 (E40) | |

Range of color temperature: 2700/3500/4000/5000/6500
Color index CRI>80 (Ra)

Induction Lighting: 50W Self Ballasted (E27/E40 Base)

Induction Lamp (50W)

V Series:

Compact ballast design, low wattage (50W)

International standard Edison lamp base.

It can match voltage AC: 120V、220V、277V、



1. Special mushroom shape structure, luminous points focus, uniform light emission in 360 degree space.
2. Bigger light surface area than other lamps with the same wattage, soft light.
3. Compact integrated structure, match for all kinds of small size lighting fixtures, and perform lighting effects of different spatial place.
4. Spiral lamp base, easily to retrofit all kinds of compact lamps.
5. Special magnetic hoop structure, effectively avoid magnetic leakage and magnetic core power loss, perfect heat dissipation ability.
6. Special ferrite magnetic core, maintain the magnetic core inductance stable in wide temperature range; unique B-H curve, reduce the magnetic hysteresis loss and magnetic core loss.
7. Amalgam inside, less pollution, eco-friendly.
8. Special amalgam, well suited for the instant-start features and stability characteristics in the wide range of temperature.
9. With special technology, power start faster, better stability.
10. Self-developed inert gas formula, ensure the consistency of light efficiency and power.
11. Full range of color temperature, a variety of power options
12. Inside compact electronic ballast, unique ballast technology, improve the power factor.
13. Special winding technology, improve the low temperature start ability.
14. We can produce variety of wattage upon the customers' special requirement.

Specifications of LVD Induction Lamp

| Series | Type | Warr. (Year) | Volts(V) | Rated luminous flux(Lm) | Pupil luminous flux (Plm) | Lamp specification(mm) | Wattage(W) |
|--------|------|--------------|------------------------------|-------------------------|---------------------------|------------------------|------------|
| V | V-50 | 5 | 220/120/ 277/347 12/24 | 3900 | 5850~6900 | 115x88x241(E27) | 50 |
| | | | | | | 115x88x261(E40) | |

Range of color temperature: 2700K/3500K/4000K/5000K/6500K

Color index CRI>80 (Ra)

Packing information

| ITEM | Out Packing Size(mm) | | Weight(KG) | | Lamp base | Packing of Carton | |
|------|----------------------|---------|------------|---------|-----------|---------------------------|---------|
| | Tube | Ballast | Tube | Ballast | | Tube | Ballast |
| V-50 | 130*150*290 | inside | 0.676 | inside | E40/E27 | 810*318*608/carton(24pcs) | inside |



Eco-Smart, Inc.
4411 Bee Ridge Rd. #344
Sarasota, FL 34233
888-329-2705 ph / 941-377-9460 fx
www.eco-smart.com

**Induction 40W and 50W Self Ballasted Lamps
Wholesale Price List**

| Model | Description | Qty | | |
|--------------|---|---------------|-----------------|------------------|
| | | 1 to 9 | 10 to 19 | 20 and up |
| 40W-V | 40W Self Ballasted Induction Lamp (2600 Lumens / 4600 Pupil Lumens) | \$74.00 | \$67.27 | \$61.67 |
| 50W-V | 50W Self Ballasted Induction Lamp (3900 Lumens / 6900 Pupil Lumens) | \$104.80 | \$95.27 | \$87.33 |

Options: Please indicate Voltage (12, 24, 120, 220, 277, 347)

Please indicate E40 or E27 base

Freight: Quoted by job, lead time approximately 2 weeks

Terms: Prepaid by credit card, check or wire transfer

