Item No.	Photo	Technical factors 01	Technical factors 02	Replaces HID	Wholesale Price (USD)
ECO-HB-30W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 30W System Power: 33W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 2700LM Lifetime: >50000H Material:aluminum alloy Product size: Ф525mm*H550mm Lamp shade: Ф525mm Weight: 5.5g	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、120° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/4m: >184Lux Average illumination/6m: >136Lux Effective illuminated Area/4m: ¢ 4.1M Effective illuminated Area/6m: ¢ 6.8M	100 to 125W	\$140.00
ECO-HB-50W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 50W System Power: 55W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 4500LM Lifetime: >50000H Material:aluminum alloy Product size: Ф525mm*H550mm Lamp shade: Ф525mm Weight: 6kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、120° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/5m: >142Lux Average illumination/6m: >71Lux Effective illuminated Area/5m: ¢ 5.1M Effective illuminated Area/6m: ¢ 6.8M	150 to 200W	\$180.00

Item No.	Photo	Technical factors 01	Technical factors 02	Replaces HID	Wholesale Price (USD)
ECO-HB-80W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 80W System Power: 88W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 7200LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H560mm Lamp shade: Ф470mm Weight: 6kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、120° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/10m: >160LX Average illumination/12m: >130LX Effective illuminated Area/6m: ¢ 5.8M Effective illuminated Area/8m: ¢ 8.2M	250 to 320W	\$240.00
ECO-HB-90W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 90W System Power: 105W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 9000LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H510mm Lamp shade: Ф470mm Weight: 6.5kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、60° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/8m: > Average illumination/10m: > Effective illuminated Area/8m: ¢ 7.8M Effective illuminated Area/10m: ¢ 9.2M	250 to 350W	\$270.00

Item No.	Photo	Technical factors 01	Technical factors 02	Replaces HID	Wholesale Price (USD)
ECO-HB-100W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 100W System Power: 110W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 9000LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H560mm Lamp shade: Ф470mm Weight: 6kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、120° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/8m: > Average illumination/10m: > Effective illuminated Area/8m: ¢ 7.8M Effective illuminated Area/10m: ¢ 9.2M	320 to 400W	\$290.00
ECO-HB-120W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 120W System Power: 145W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 10800LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H510mm Lamp shade: Ф470mm Weight: 7.5kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、60° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/10m: >185LX Average illumination/12m: >120LX Effective illuminated Area/10m:	350 to 450W	\$320.00

Item No.	Photo	Technical factors 01	Technical factors 02	Replaces HID	Wholesale Price (USD)
ECO-HB-150W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 150W System Power: 178W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35 °C Lumen: 13500LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H510mm Lamp shade: Ф470mm Weight: 7.5kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、60° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/10m: >190LX Average illumination/12m: >160LX Effective illuminated Area/10m: ¢ 9.8M Effective illuminated Area/12m: ¢ 11.2M	450 to 600W	\$390.00
ECO-HB-180W		U.S. Made Bridgelux LEDs Voltage: AC110-265V/50HZ Led power: 180W System Power: 206W Color temperature: 2500-10000K CRI:Ra > 75 Temperature: 50/-35°C Lumen: 16200LM Lifetime: >50000H Material:aluminum alloy Product size: Ф470mm*H510mm Lamp shade: Ф470mm Weight: 7.5kg	UL Driver, 5 Year Warranty IP54: IP54 Angle: 45°、60° THD: ≤9% Power factor: > 0.98 Power supply efficiency: 82% Light efficency: 91% Average illumination/12m: >230LX Average illumination/14m: >180LX Effective illuminated Area/12m: ¢ 11.8M Effective illuminated Area/14m: ¢ 13.2M	500 to 750W	\$420.00