

LED Spots, LED Globe Bulbs, LED Chandelier Bulbs

TYPE	PICTURE	KEY SPECIFICATIONS	PRICE
MR16		Product No: SLMR16-01W Voltage: AC/DC12V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 320 lm CRI: ≥70 Ra Color Temperature: WW 2700 – 3500K Base: GU5.3 Beam Angle: 60°	\$27.00
MR16		Product No: SLMR16-01N Voltage: AC/DC12V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 360 lm CRI: ≥70 Ra Color Temperature: NW 4500 – 5500K Base: GU5.3 Beam Angle: 60°	\$27.00
MR16 DIMMABLE		Product No: SLMR16-02W-D Voltage: 12V Power Consumption: 6W LED: 1 Pcs Luminous Flux: 320 lm Dimmable 50% Color Temperature: WW 2600 – 3000K Base: GU10 Beam Angle: 30°, 60°	\$29.00
MR16 DIMMABLE		Product No: SLMR16-02C-D Voltage: 12V Power Consumption: 6W LED: 1 Pcs Luminous Flux: 350 lm Dimmable 50% Color Temperature: CW 5300 – 7000K Base: MR16 Beam Angle: 30°, 60°	\$29.00
MR16		Product No: SLMR16-03W Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 250 lm Color Temperature: WW 2800 – 3200K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°	\$24.00
MR16		Product No: SLMR16-03N Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 270 lm Color Temperature: NW 3500 – 4000K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°	\$24.00

LED Spots, LED Globe Bulbs, LED Chandelier Bulbs

MR16		<p>Product No: SLMR16-03C Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 300 lm Color Temperature: CW 5000 – 6500K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°</p>	\$24.00
MR16 DIMMABLE		<p>Product No: SLMR16-03W-D Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 250 lm Dimmable with inline potentiometer dimmers Color Temperature: WW 2800 – 3200K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°</p>	\$30.00
MR16 DIMMABLE		<p>Product No: SLMR16-03N-D Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 270 lm Dimmable with inline potentiometer dimmers Color Temperature: NW 3500 – 4000K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°</p>	\$30.00
MR16 DIMMABLE		<p>Product No: SLMR16-03C-D Voltage: 12V DC Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 300 lm Dimmable with inline potentiometer dimmers Color Temperature: CW 5000 – 6500K CE, cUL/UL, RoHS Beam Angle: 15°, 30°, 45°, 60°</p>	\$30.00
GU10		<p>Product No: SLGU10-01W Voltage: AC110-240V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 320 lm CRI: ≥70 Ra Color Temperature: WW 2700 – 3500K Base: GU10 Beam Angle: 60°</p>	\$29.00
GU10		<p>Product No: SLGU10-01N Voltage: AC110-240V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 360 lm CRI: ≥70 Ra Color Temperature: NW 4500 – 5000K Base: GU10 Beam Angle: 60°</p>	\$29.00







LED Spots, LED Globe Bulbs, LED Chandelier Bulbs

GU10 DIMMABLE		Product No: SLGU10-02W-D Voltage: AC 110-240V Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 250 lm Dimmable Color Temperature: WW 2800 - 3200K Dimensions: Ø50 X H60 CE, cUL/UL, RoHS 3 Year Warranty Beam Angle: 15°, 30°, 45°, 60°	\$30.00
GU10 DIMMABLE		Product No: SLGU10-02N-D Voltage: AC 110-240V Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 270 lm Dimmable Color Temperature: NW 3500 - 4000K Dimensions: Ø50 X H60 CE, cUL/UL, RoHS 3 Year Warranty Beam Angle: 15°, 30°, 45°, 60°	\$30.00
GU10 DIMMABLE		Product No: SLGU10-02C-D Voltage: AC 110-240V Power Consumption: 5W LED: 3 Pcs x 3W CREE XPE or XRE Luminous Flux: 300 lm Dimmable Color Temperature: CW 5000 - 6500K Dimensions: Ø50 X H60 CE, cUL/UL, RoHS 3 Year Warranty Beam Angle: 15°, 30°, 45°, 60°	\$30.00
GU10 DIMMABLE		Product No: SLGU10-03W-D Voltage: AC110-240V Power Consumption: 5W LED: 5 Pcs Luminous Flux: 320 lm +/- 10% Color Temperature: NW 3000 - 3500K Dimmable Base: GU10 Beam Angle: 45°	\$29.00
GU10 DIMMABLE		Product No: SLGU10-03N-D Voltage: AC110-240V Power Consumption: 5W LED: 5 Pcs Luminous Flux: 340 lm +/- 10% Color Temperature: NW 4000 - 4500K Dimmable Base: GU10 Beam Angle: 45°	\$29.00
MINI SPOT		Product No: SLE27-01W Voltage: AC110-240V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 320 lm CRI: ≥70 Ra Color Temperature: WW 2700 - 3500K Base: E27 Beam Angle: 60°	\$29.00

LED Spots, LED Globe Bulbs, LED Chandelier Bulbs

<p style="text-align: center;">MINI SPOT</p>		<p>Product No: SLE27-01N Voltage: AC110-240V Power Consumption: 4W LED: 3 Pcs Luminous Flux: 360 lm CRI: ≥70 Ra Color Temperature: NW 4500 – 5000K Base: E27 Beam Angle: 60°</p>	<p style="text-align: center;">\$29.00</p>
<p style="text-align: center;">GLOBE</p>		<p>Product No: SLA19-01W Voltage: AC110-240V Power Consumption: 5W Luminous Flux: 300 lm CRI: ≥80 Ra Color Temperature: WW 2800K Base: E27 Beam Angle: 270°</p>	<p style="text-align: center;">\$11.00</p>
<p style="text-align: center;">GLOBE</p>		<p>Product No: SLA19-01N Voltage: AC110-240V Power Consumption: 5W Luminous Flux: 340 lm CRI: ≥80 Ra Color Temperature: NW 4000K Base: E27 Beam Angle: 270°</p>	<p style="text-align: center;">\$11.00</p>
<p style="text-align: center;">GLOBE</p>		<p>Product No: SLA19-01C Voltage: AC110-240V Power Consumption: 5W Luminous Flux: 360 lm CRI: ≥80 Ra Color Temperature: CW 5600K Base: E27 Beam Angle: 270°</p>	<p style="text-align: center;">\$11.00</p>
<p style="text-align: center;">GLOBE DIMMABLE</p>		<p>Product No: SLA19-03W-D Voltage: AC110-140V Power Consumption: 8W LED Chips: LG 14 x 0.5W Luminous Flux: 400 lm Dimensions: Φ60*116 Color Temperature: WW 2800K Base: E27 DIMMABLE</p>	<p style="text-align: center;">\$23.00</p>
<p style="text-align: center;">GLOBE DIMMABLE</p>		<p>Product No: SLA19-03N-D Voltage: AC110-140V Power Consumption: 8W LED Chips: LG 14 x 0.5W Luminous Flux: 450 lm Dimensions: Φ60*116 Color Temperature: NW 4500K Base: E27 DIMMABLE</p>	<p style="text-align: center;">\$23.00</p>

LED Spots, LED Globe Bulbs, LED Chandelier Bulbs

GLOBE DIMMABLE		Product No: SLA19-04W-D Voltage: AC90-264V Power Consumption: 7.7W Viewing Angle: 210° Luminous Flux: 288-432 lm (360 Typical) Dimensions: Φ60*112 Color Temperature: WW 2550K-3450K Base: E27 DIMMABLE	\$25.00
GLOBE DIMMABLE		Product No: SLA19-04N-D Voltage: AC90-264V Power Consumption: 7.7W Viewing Angle: 210° Luminous Flux: 360-540 lm (450 Typical) Dimensions: Φ60*112 Color Temperature: NW 4250K-5750K Base: E27 DIMMABLE	\$25.00
CANDELABRA		Product No: SLCL-01W Voltage: AC110-240V Power Consumption: 4W Luminous Flux: 280 lm CRI: ≥80 Ra Color Temperature: WW 3000K-3500K Base: E14 (E12 base available) Beam Angle: 270°	\$16.00
CANDELABRA		Product No: SLCL-01N Voltage: AC110-240V Power Consumption: 4W Luminous Flux: 300 lm CRI: ≥80 Ra Color Temperature: NW 4500K-5000K Base: E14 (E12 base available) Beam Angle: 270°	\$16.00
CANDELABRA DIMMABLE		Product No: SLCLT-02W-D Voltage: AC120V Power Consumption: 2.2W (equivalent to 25W) Torpedo Shape - Clear (also available in frosted) CRI: ≥60 Ra Color Temperature: Warm 2800K Base: E12 Beam Angle: 360°	\$11.00
CANDELABRA DIMMABLE		Product No: SLCLF-02W-D Voltage: AC120V Power Consumption: 2.2W (Equivalent to 25W) Flame Tip - Clear (also available in frosted) CRI: ≥60 Ra Color Temperature: Warm 2800K Base: E12 Beam Angle: 360°	\$11.00

LED Par Bulbs, LED Down Lights

TYPE	PICTURE	KEY SPECIFICATIONS	PRICE
PAR20		Product No: SLPAR20-01W Voltage: AC110-240V Power Consumption: 5W LED: 3 Pcs Luminous Flux: 400 lm CRI: ≥ 70 Ra Color Temperature: WW 2700 - 3500K Base: E27 Beam Angle: 60° CE, cUL/UL, RoHS	\$29.00
PAR20		Product No: SLPAR20-01N Voltage: AC110-240V Power Consumption: 5W LED: 3 Pcs Luminous Flux: 450 lm CRI: ≥ 70 Ra Color Temperature: NW 4500K - 5500K Base: E27 Beam Angle: 60° CE, cUL/UL, RoHS	\$29.00
PAR20		Product No: SLPAR20-02W Voltage: AC100-240V Power Consumption: 7W LED: 5 x 1W Luminous Flux: 260 lm Color Temperature: WW 2700K-3300K Dimensions: $\phi 64.5 \times H91$ Base: E27 CE, cUL/UL, RoHS	\$31.00
PAR20		Product No: SLPAR20-02N Voltage: AC100-240V Power Consumption: 7W LED: 5 x 1W Luminous Flux: 350 lm Color Temperature: NW 4000K-4500K Dimensions: $\phi 64.5 \times H91$ Base: E27 CE, cUL/UL, RoHS	\$31.00
PAR20		Product No: SLPAR20-02C Voltage: AC100-240V Power Consumption: 7W LED: 5 x 1W Luminous Flux: 400 lm Color Temperature: CW 5000K-6000K Dimensions: $\phi 64.5 \times H91$ Base: E27 CE, cUL/UL, RoHS	\$31.00
PAR20 WATER RESISTANT		Product No: SLPROPAR20W Voltage: AC100-240V LED: 9W CREE Luminous Flux: 400 lm Dimensions: $\phi 64 \times H90$ Color Temperature: WW 2800K-3300K Beam Angle: 24° IP66 CE, cUL/UL, RoHS	\$46.00

Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com

LED Par Bulbs, LED Down Lights

<p style="text-align: center;">PAR20 WATER RESISTANT</p>		<p>Product No: SLPROPAR20C Voltage: AC100-240V LED: 9W CREE Luminous Flux: 430 lm Dimensions: φ64*H90 Color Temperature: CW 5500K-6500K Beam Angle: 24° IP66 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$46.00</p>
<p style="text-align: center;">PAR20</p>		<p>Product No: SLPAR20-03W Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 290 lm Color Temperature: WW 3000K Beam Angle: 15°, 25°, 40° Dimensions: φ63.5*H95 Base: E27 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$28.00</p>
<p style="text-align: center;">PAR20</p>		<p>Product No: SLPAR20-03N Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 348 lm Color Temperature: NW 4000K Beam Angle: 15°, 25°, 40° Dimensions: φ63.5*H95 Base: E27 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$28.00</p>
<p style="text-align: center;">PAR20</p>		<p>Product No: SLPAR20-03C Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 363 lm Color Temperature: CW 5500K-6000K Beam Angle: 15°, 25°, 40° Dimensions: φ63.5*H95 Base: E27 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$28.00</p>
<p style="text-align: center;">PAR20 DIMMABLE</p>		<p>Product No: SLPAR20-04W-D Voltage: AC110V Power Consumption: 5W LED: 5 Pcs Dimmable Color Temperature: WW 3500K Base: E26/E27 Beam Angle: 30° or 60°</p>	<p style="text-align: center;">\$32.00</p>
<p style="text-align: center;">PAR20 DIMMABLE</p>		<p>Product No: SLPAR20-04N-D Voltage: AC110V Power Consumption: 5W LED: 5 Pcs Dimmable Color Temperature: NW 4500K Base: E26/E27 Beam Angle: 30° or 60°</p>	<p style="text-align: center;">\$32.00</p>

LED Par Bulbs, LED Down Lights

PAR20 DIMMABLE		Product No: SLPAR20-05W-D Voltage: AC120V LED: 3 x 3W CREE – 9 Watts Luminous Flux: 260 lm Color Temperature: WW 2800K-3000K Dimmable Dimensions: Φ63*H87 Available in Black or Silver Finish Base: E27 CE, cUL/UL, RoHS	\$52.00
PAR20 DIMMABLE		Product No: SLPAR20-05C-D Voltage: AC120V LED: 3 x 3W CREE – 9 Watts Luminous Flux: 320 lm Color Temperature: CW 5500K-6500K Dimmable Dimensions: Φ63*H87 Available in Black or Silver Finish Base: E27 CE, cUL/UL, RoHS	\$52.00
PAR20 DIMMABLE		Product No: SLPAR20-06W-D Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 290 lm Color Temperature: WW 3000K Dimmable 5% to 100% Beam Angle: 15°, 25°, 40° Dimensions: Φ63.5*H95 CE, cUL/UL, RoHS	\$33.00
PAR20 DIMMABLE		Product No: SLPAR20-06N-D Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 348 lm Color Temperature: NW 4000K Dimmable 5% to 100% Beam Angle: 15°, 25°, 40° Dimensions: Φ63.5*H95 CE, cUL/UL, RoHS	\$33.00
PAR20 DIMMABLE		Product No: SLPAR20-06C-D Voltage: AC110V Power Consumption: 7W LED: 3 x 2W CREE Luminous Flux: 363 lm Color Temperature: CW 5500K-6000K Dimmable 5% to 100% Beam Angle: 15°, 25°, 40° Dimensions: Φ63.5*H95 CE, cUL/UL, RoHS	\$33.00
PAR30		Product No: SLPAR30-01W Voltage: AC85-265V Power Consumption: 8W LED: 6 x 1W Bridgelux Luminous Flux: 450 lm +/- 10% CRI: ≥80 Ra Color Temperature: WW 3000K CE, cUL/UL	\$53.00

LED Par Bulbs, LED Down Lights

PAR30		<p>Product No: SLPAR30-01N Voltage: AC85-265V Power Consumption: 8W LED: 6 x 1W Bridgelux Luminous Flux: 480 lm +/- 10% CRI: ≥80 Ra Color Temperature: NW 4500K CE, cUL/UL</p>	\$53.00
PAR30		<p>Product No: SLPAR30-02W Voltage: AC110-240V Power Consumption: 9W LED: 7 Pcs Luminous Flux: 720 lm CRI: ≥70 Ra Color Temperature: WW 2700 - 3500K Base: E27 Beam Angle: 60° CE, cUL/UL</p>	\$55.00
PAR30		<p>Product No: SLPAR30-02N Voltage: AC110-240V Power Consumption: 9W LED: 7 Pcs Luminous Flux: 810 lm CRI: ≥70 Ra Color Temperature: NW 4500K - 5500K Base: E27 Beam Angle: 60° CE, cUL/UL</p>	\$55.00
PAR30		<p>Product No: SLPAR30-03W Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 580 lm Color Temperature: WW 3000K Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30		<p>Product No: SLPAR30-03N Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 696 lm Color Temperature: NW 4000K-4500K Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30		<p>Product No: SLPAR30-03C Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 725 lm Color Temperature: CW 5500K-6000K Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00

LED Par Bulbs, LED Down Lights

PAR30		<p>Product No: SLPAR30-04W Voltage: AC100-240V LED: 9 x 1W - 9 Watt Luminous Flux: 520 lm Color Temperature: WW 2700K-3300K Dimensions: φ95*H90.5 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30		<p>Product No: SLPAR30-04N Voltage: AC100-240V LED: 9 x 1W - 9 Watt Luminous Flux: 620 lm Color Temperature: NW 4000K-4500K Dimensions: φ95*H90.5 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30		<p>Product No: SLPAR30-04C Voltage: AC100-240V LED: 9 x 1W - 9 Watt Luminous Flux: 700 lm Color Temperature: CW 5000K-6000K Dimensions: φ95*H90.5 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30		<p>Product No: SLPAR30-05W Voltage: AC90-130V LED: 5 x 3W CREE - 9 Watt Luminous Flux: 475 lm Color Temperature: WW 2700K-3300K Dimensions: φ95*H97 Base: E27 CE, cUL/UL, RoHS</p>	\$51.00
PAR30		<p>Product No: SLPAR30-05N Voltage: AC90-130V LED: 5 x 3W CREE - 9 Watt Luminous Flux: 550 lm Color Temperature: NW 4000K-4500K Dimensions: φ95*H97 Base: E27 CE, cUL/UL, RoHS</p>	\$51.00
PAR30		<p>Product No: SLPAR30-05C Voltage: AC90-130V LED: 5 x 3W CREE - 9 Watt Luminous Flux: 650 lm Color Temperature: CW 5000K-6000K Dimensions: φ95*H97 Base: E27 CE, cUL/UL, RoHS</p>	\$51.00

LED Par Bulbs, LED Down Lights

<p>PAR30 IP66 – WATER RESISTANT</p>		<p>Product No: SLPROPAR30W Voltage: AC100–240V LED: 13W CREE Luminous Flux: 520 lm Dimensions: ϕ95*H90 Color Temperature: WW 2800K–3300K Beam Angle: 30° IP66 Water Resistant CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$71.00</p>
<p>PAR30 IP66 – WATER RESISTANT</p>		<p>Product No: SLPROPAR30C Voltage: AC100–240V LED: 13W CREE Luminous Flux: 560 lm Dimensions: ϕ95*H90 Color Temperature: CW 5500K–6500K Beam Angle: 30° IP66 Water Resistant CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$71.00</p>
<p>PAR30 DIMMABLE</p>		<p>Product No: SLPAR30–01W–D Voltage: AC85–265V Power Consumption: 8W LED: 6 x 1W Bridgelux Luminous Flux: 450 lm +/- 10% CRI: ≥80 Ra Dimmable Color Temperature: WW 3000K CE, cUL/UL</p>	<p style="text-align: center;">\$56.00</p>
<p>PAR30 DIMMABLE</p>		<p>Product No: SLPAR30–01N–D Voltage: AC85–265V Power Consumption: 8W LED: 6 x 1W Bridgelux Luminous Flux: 480 lm +/- 10% CRI: ≥80 Ra Dimmable Color Temperature: NW 4500K CE, cUL/UL</p>	<p style="text-align: center;">\$56.00</p>
<p>PAR30 DIMMABLE</p>		<p>Product No: SLPAR30–06W–D Voltage: AC110V Power Consumption: 14W LED: 5 x 2W CREE XPE Luminous Flux: 530 lm Color Temperature: WW 3000K Dimmable 5% to 100% Beam Angle: 25°, 40°, 60° Dimensions: ϕ95*H112 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$57.00</p>
<p>PAR30 DIMMABLE</p>		<p>Product No: SLPAR30–06N–D Voltage: AC110V Power Consumption: 14W LED: 5 x 2W CREE XPE Luminous Flux: 636 lm Color Temperature: NW 4000K–4500K Dimmable 5% to 100% Beam Angle: 25°, 40°, 60° Dimensions: ϕ95*H112 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$57.00</p>

LED Par Bulbs, LED Down Lights

PAR30 DIMMABLE		<p>Product No: SLPAR30-06C-D Voltage: AC110V Power Consumption: 14W LED: 5 x 2W CREE XPE Luminous Flux: 663 lm Color Temperature: CW 5500K-6000K Dimmable 5% to 100% Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 CE, cUL/UL, RoHS</p>	\$57.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-07W-D Voltage: AC100-240V LED: 5 x 3W CREE - 15 Watt Luminous Flux: 580 lm Dimensions: φ94*H90 Color Temperature: WW 2800K-3000K Available in Black or Silver Finish Beam Angle: 40°, 60°, 80° Dimmable CE, cUL/UL, RoHS</p>	\$77.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-07N-D Voltage: AC100-240V LED: 5 x 3W CREE - 15 Watt Luminous Flux: 650 lm Dimensions: φ94*H90 Color Temperature: WW 3500K-4000K Available in Black or Silver Finish Beam Angle: 40°, 60°, 80° Dimmable CE, cUL/UL, RoHS</p>	\$77.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-07C-D Voltage: AC100-240V LED: 5 x 3W CREE - 15 Watt Luminous Flux: 760 lm Dimensions: φ94*H90 Color Temperature: CW 5000K-6500K Available in Black or Silver Finish Beam Angle: 40°, 60°, 80° Dimmable CE, cUL/UL, RoHS</p>	\$77.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-03W-D Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 580 lm Color Temperature: WW 3000K Dimmable 5%-100% Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 CE, cUL/UL, RoHS</p>	\$67.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-03N-D Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 696 lm Color Temperature: NW 4000K-4500K Dimmable 5%-100% Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 CE, cUL/UL, RoHS</p>	\$67.00







LED Par Bulbs, LED Down Lights

PAR30 DIMMABLE		<p>Product No: SLPAR30-03C-D Voltage: AC110V Power Consumption: 14W LED: 7 x 2W CREE XPE Luminous Flux: 725 lm Color Temperature: CW 5500K-6000K Dimmable 5%-100% Beam Angle: 25°, 40°, 60° Dimensions: φ95*H112 CE, cUL/UL, RoHS</p>	\$67.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-09W-D Voltage: AC110-240V LED: 5 x 3W CREE - 13 Watts Luminous Flux: 580 lm Dimensions: φ94*H95 Color Temperature: WW 2800K-3200K Available in Black or Silver Finish Beam Angle: 25°, 40° Dimmable CE, cUL/UL, RoHS</p>	\$81.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-09N-D Voltage: AC110-240V LED: 5 x 3W CREE - 13 Watts Luminous Flux: 650 lm Dimensions: φ94*H95 Color Temperature: NW 3500K-4000K Available in Black or Silver Finish Beam Angle: 25°, 40° Dimmable CE, cUL/UL, RoHS</p>	\$81.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-09C-D Voltage: AC110-240V LED: 5 x 3W CREE - 13 Watts Luminous Flux: 760 lm Dimensions: φ94*H95 Color Temperature: CW 5000K-6500K Available in Black or Silver Finish Beam Angle: 25°, 40° Dimmable CE, cUL/UL, RoHS</p>	\$81.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-10W-D Voltage: AC90-130V LED: 5 x 3W CREE Power: 9 Watts Luminous Flux: 475 lm Color Temperature: WW 2700K-3300K Dimmable Dimensions: φ95*H100 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR30 DIMMABLE		<p>Product No: SLPAR30-10N-D Voltage: AC90-130V LED: 5 x 3W CREE Power: 9 Watts Luminous Flux: 550 lm Color Temperature: NW 4000K-4500K Dimmable Dimensions: φ95*H100 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00

LED Par Bulbs, LED Down Lights

PAR30 DIMMABLE		<p>Product No: SLPAR30-10C-D Voltage: AC90-130V LED: 5 x 3W CREE Power: 9 Watts Luminous Flux: 650 lm Color Temperature: CW 5000K-6000K Dimmable Dimensions: ϕ95*H100 Base: E27 CE, cUL/UL, RoHS</p>	\$55.00
PAR38		<p>Product No: SLPAR38-01W Voltage: AC85-265V Power Consumption: 12W LED: 9 Pcs Luminous Flux: 675 lm +/- 10% CRI: \geq80 Ra Color Temperature: WW 3000K Base: E27 cUL/UL</p>	\$66.00
PAR38		<p>Product No: SLPAR38-01N Voltage: AC85-265V Power Consumption: 12W LED: 9 Pcs Luminous Flux: 720 lm +/- 10% CRI: \geq80 Ra Color Temperature: NW 4500K Base: E27 cUL/UL</p>	\$66.00
PAR38		<p>Product No: SLPAR38-02W Voltage: AC110-240V cUL/UL Power Consumption: 17W LED: 10 Pcs Luminous Flux: 1360 lm CRI: \geq70 Ra Color Temperature: WW 2700K - 3500K Base: E27 Beam Angle: 60°</p>	\$70.00
PAR38		<p>Product No: SLPAR38-02N Voltage: AC110-240V cUL/UL Power Consumption: 17W LED: 10 Pcs Luminous Flux: 1530 lm CRI: \geq70 Ra Color Temperature: NW 4500K - 5500K Base: E27 Beam Angle: 60°</p>	\$70.00
PAR38		<p>Product No: SLPAR38-03W Voltage: AC100-240V cUL/UL Power Consumption: 15W LED: 15 Pcs Luminous Flux: 880 lm CRI: \geq70 Ra Color Temperature: WW 2700K - 3300K ϕ130*H121 Beam Angle: 60°</p>	\$91.00

LED Par Bulbs, LED Down Lights

PAR38		<p>Product No: SLPAR38-03N Voltage: AC100-240V cUL/UL Power Consumption: 15W LED: 15 Pcs Luminous Flux: 1000 lm CRI: ≥70 Ra Color Temperature: WW 4000K - 4500K Φ130*H121 Beam Angle: 60°</p>	\$91.00
PAR38		<p>Product No: SLPAR38-03C Voltage: AC100-240V cUL/UL Power Consumption: 15W LED: 15 Pcs Luminous Flux: 1200 lm CRI: ≥70 Ra Color Temperature: WW 5000K - 6000K Φ130*H121 Beam Angle: 60°</p>	\$91.00
PAR38		<p>Product No: SLPAR38-04W Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 720 lm CRI: ≥82 Ra Color Temperature: WW 3000K - 3500K Base: E27 Beam Angles Available: 25°, 40°, 60°</p>	\$85.00
PAR38		<p>Product No: SLPAR38-04N Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 864 lm CRI: ≥82 Ra Color Temperature: NW 4000K - 4500K Base: E27 Beam Angles Available: 25°, 40°, 60°</p>	\$85.00
PAR38		<p>Product No: SLPAR38-04C Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 900 lm CRI: ≥82 Ra Color Temperature: CW 5500K - 6000K Base: E27 Beam Angles Available: 25°, 40°, 60°</p>	\$85.00
PAR38 IP66 - WATER RESISTANT		<p>Product No: SLPROPAR38W Voltage: AC100-240V LED: 18W CREE Luminous Flux: 640 lm Dimensions: Φ120*H134.5 Color Temperature: WW 2800K-3300K Beam Angle: 30° IP66 CE, cUL/UL, RoHS</p>	\$73.00

LED Par Bulbs, LED Down Lights

<p style="text-align: center;">PAR38 IP66 – WATER RESISTANT</p>		<p>Product No: SLPROPAR38C Voltage: AC100-240V LED: 18W CREE Luminous Flux: 680 lm Dimensions: ϕ120*H134.5 Color Temperature: CW 5500K-6500K Beam Angle: 30° IP66 CE, cUL/UL, RoHS</p>	<p style="text-align: center;">\$73.00</p>
<p style="text-align: center;">PAR38 DIMMABLE</p>		<p>Product No: SLPAR38-01W-D Voltage: AC85-265V Power Consumption: 12W LED: 9 Pcs Luminous Flux: 675 lm +/- 10% CRI: \geq80 Ra Color Temperature: WW 3000K DIMMABLE 5%-100% Base: E27 cUL/UL</p>	<p style="text-align: center;">\$70.00</p>
<p style="text-align: center;">PAR38 DIMMABLE</p>		<p>Product No: SLPAR38-01N-D Voltage: AC85-265V Power Consumption: 12W LED: 9 Pcs Luminous Flux: 720 lm +/- 10% CRI: \geq80 Ra Color Temperature: NW 4500K DIMMABLE 5%-100% Base: E27 cUL/UL</p>	<p style="text-align: center;">\$70.00</p>
<p style="text-align: center;">PAR38 REFLECTOR DIMMABLE</p>		<p>Product No: SLPAR38REF-W-D Voltage: AC110V cUL/UL Power Consumption: 18W LED: 7 Pcs CREE HEW Luminous Flux: 680 lm CRI: \geq82 Ra Color Temperature: WW 3000K - 3500K DIMMABLE 5%-100% Dimensions: ϕ120.5*H135 Beam Angles Available: 25°, 40°</p>	<p style="text-align: center;">\$72.00</p>
<p style="text-align: center;">PAR38 REFLECTOR DIMMABLE</p>		<p>Product No: SLPAR38REF-N-D Voltage: AC110V cUL/UL Power Consumption: 18W LED: 7 Pcs CREE HEW Luminous Flux: 810 lm CRI: \geq82 Ra Color Temperature: NW 4000K - 4500K DIMMABLE 5%-100% Dimensions: ϕ120.5*H135 Beam Angles Available: 25°, 40°</p>	<p style="text-align: center;">\$72.00</p>
<p style="text-align: center;">PAR38 REFLECTOR DIMMABLE</p>		<p>Product No: SLPAR38REF-C-D Voltage: AC110V cUL/UL Power Consumption: 18W LED: 7 Pcs CREE HEW Luminous Flux: 850 lm CRI: \geq75 Ra Color Temperature: CW 5500K - 6500K DIMMABLE 5%-100% Dimensions: ϕ120.5*H135 Beam Angles Available: 25°, 40°</p>	<p style="text-align: center;">\$72.00</p>

LED Par Bulbs, LED Down Lights

PAR38 DIMMABLE		Product No: SLPAR38-05W-D Voltage: AC120V LED: 7 x 3W CREE – 17 Watt Luminous Flux: 850 lm Dimensions: ϕ 121*H139 Color Temperature: WW 2800K-3000K Available in Black or Silver Finish DIMMABLE – (Non-Dimmable Available) Beam Angles Available: 25°, 40°, 60°, 80° cUL/UL, CE, RoHS	\$105.00
PAR38 DIMMABLE		Product No: SLPAR38-05N-D Voltage: AC120V LED: 7 x 3W CREE – 17 Watt Luminous Flux: 950 lm Dimensions: ϕ 121*H139 Color Temperature: NW 3500K-4000K Available in Black or Silver Finish DIMMABLE – (Non-Dimmable Available) Beam Angles Available: 25°, 40°, 60°, 80° cUL/UL, CE, RoHS	\$105.00
PAR38 DIMMABLE		Product No: SLPAR38-05C-D Voltage: AC120V LED: 7 x 3W CREE – 17 Watt Luminous Flux: 1050 lm Dimensions: ϕ 121*H139 Color Temperature: CW 5500K-6500K Available in Black or Silver Finish DIMMABLE – (Non-Dimmable Available) Beam Angles Available: 25°, 40°, 60°, 80° cUL/UL, CE, RoHS	\$105.00
PAR38 DIMMABLE		Product No: SLPAR38-06W-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 9 Pcs CREE XPE Luminous Flux: 645 lm CRI: \geq 82 Ra Color Temperature: WW 3000K – 3500K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$90.00
PAR38 DIMMABLE		Product No: SLPAR38-06N-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 9 Pcs CREE XPE Luminous Flux: 760 lm CRI: \geq 82 Ra Color Temperature: NW 4000K – 4500K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$90.00
PAR38 DIMMABLE		Product No: SLPAR38-06C-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 9 Pcs CREE XPE Luminous Flux: 810 lm CRI: \geq 82 Ra Color Temperature: CW 5500K – 6000K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$90.00

LED Par Bulbs, LED Down Lights

PAR38 DIMMABLE		<p>Product No: SLPAR38-07W-D Voltage: AC90-130V LED: 9 x 3W CREE MX6 or XPE - 13 Watt Luminous Flux: 840 lm Dimensions: ϕ120*H125 Color Temperature: WW 2700K-3300K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$93.00
PAR38 DIMMABLE		<p>Product No: SLPAR38-07N-D Voltage: AC90-130V LED: 9 x 3W CREE MX6 or XPE - 13 Watt Luminous Flux: 920 lm Dimensions: ϕ120*H125 Color Temperature: NW 4000K-4500K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$93.00
PAR38 DIMMABLE		<p>Product No: SLPAR38-07C-D Voltage: AC90-130V LED: 9 x 3W CREE MX6 or XPE - 13 Watt Luminous Flux: 1020 lm Dimensions: ϕ120*H125 Color Temperature: CW 5000K-6000K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$93.00
PAR38 DIMMABLE		<p>Product No: SLPAR38-08W-D Voltage: AC90V-130V LED: 12 x 3W - 17W Luminous Flux: 1100 lm Dimensions: ϕ120*H125 Color Temperature: WW 2700K-3300K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$103.00
PAR38 DIMMABLE		<p>Product No: SLPAR38-08N-D Voltage: AC90V-130V LED: 12 x 3W - 17W Luminous Flux: 1200 lm Dimensions: ϕ120*H125 Color Temperature: NW 4000K-4500K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$103.00
PAR38 DIMMABLE		<p>Product No: SLPAR38-08C-D Voltage: AC90V-130V LED: 12 x 3W - 17W Luminous Flux: 1320 lm Dimensions: ϕ120*H125 Color Temperature: CW 5000K-6000K DIMMABLE - (Non-Dimmable Available) Base: E27 cUL/UL, CE, RoHS</p>	\$103.00







LED Par Bulbs, LED Down Lights

PAR38 DIMMABLE		Product No: SLPAR38-09W-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 720 lm CRI: ≥82 Ra Color Temperature: WW 3000K – 3500K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$98.00
PAR38 DIMMABLE		Product No: SLPAR38-09N-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 864 lm CRI: ≥82 Ra Color Temperature: NW 4000K – 4500K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$98.00
PAR38 DIMMABLE		Product No: SLPAR38-09C-D Voltage: AC110V cUL/UL Power Consumption: 15W LED: 12 Pcs CREE XPE Luminous Flux: 900 lm CRI: ≥82 Ra Color Temperature: CW 5500K – 6000K DIMMABLE (5%-100%) Base: E27 Beam Angles Available: 25°, 40°, 60°	\$98.00
AR111		Product No: SLAR111-01W Voltage: AC/DC 12-24V Power Consumption: 13W LED: SMD Luminous Flux: 420 lm IP Rating: 65 Color Temperature: WW 3000K Beam Angle: 30°	\$57.00
AR111		Product No: SLAR111-01C Voltage: AC/DC 12-24V Power Consumption: 13W LED: SMD Luminous Flux: 530 lm IP Rating: 65 Color Temperature: CW 6000K Beam Angle: 30°	\$57.00
DOWNLIGHT		Product No: SLDL-01N Voltage: AC100-240V (transformer included) Power Consumption: 12W LED: SMD 3528 Luminous Flux: 680 lm +/- 10% CRI: ≥80 Ra Color Temperature: NW 4100K Dimensions: Φ157*H35 mm Beam Angle: 170°	\$77.00

LED Par Bulbs, LED Down Lights

DOWNLIGHT		<p>Product No: SLDL-01C Voltage: AC100-240V (transformer included) Power Consumption: 12W LED: SMD 3528 Luminous Flux: 680 lm +/- 10% CRI: ≥80 Ra Color Temperature: CW 6400K Dimensions: Φ157*H35 mm Beam Angle: 170°</p>	\$77.00
DOWNLIGHT		<p>Product No: SLDL-02W Voltage: 100-240VAC (Incorporated AC to DC) Power Consumption: 7W LED: SMD Luminous Flux: 400 lm Socket: 4P Housing Color Temperature: WW 3000K Dimensions: 110mm x 53.5mm Beam Angle: 160°</p>	\$79.00
DOWNLIGHT		<p>Product No: SLDL-02C Voltage: 100-240VAC (Incorporated AC to DC) Power Consumption: 7W LED: SMD Luminous Flux: 480 lm Socket: 4P Housing Color Temperature: CW 5600K Dimensions: 110mm x 53.5mm Beam Angle: 160°</p>	\$79.00
DOWNLIGHT		<p>Product No: SLDL-03W Voltage: 100-240VAC (Incorporated AC to DC) Power Consumption: 15W LED: SMD Luminous Flux: 700 lm Socket: 4P Housing Color Temperature: WW 3000K Dimensions: 190mm x 55mm Beam Angle: 160°</p>	\$94.00
DOWNLIGHT		<p>Product No: SLDL-03C Voltage: 100-240VAC (Incorporated AC to DC) Power Consumption: 15W LED: SMD Luminous Flux: 900 lm Socket: 4P Housing Color Temperature: CW 5600K Dimensions: 190mm x 55mm Beam Angle: 160°</p>	\$94.00







LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

TYPE	PICTURE	KEY SPECIFICATIONS	PRICE
SMD3528 60LED/METER IP20 Light Strip		Product No: SLFLEXSTRIP-01C * 3528 SMD LED flexible strip * L 5000mm x W 8mm * Input Voltage: DC12V * 3.6W/Meter * Non-waterproof IP20 * SMD3528 - 60 LED/Meter * White 6000K-7000K	\$48.00
SMD3528 60LED/METER IP20 Light Strip		Product No: SLFLEXSTRIP-01W * 3528 SMD LED flexible strip * L 5000mm x W 8mm * Input Voltage: DC12V * 3.6W/Meter * Non-waterproof IP20 * SMD3528 - 60 LED/Meter * Warm White 3000K-3500K	\$48.00
SMD3528 60LED/METER IP68 Light Strip		Product No: SLFLEXSTRIP-02C-D * 3528 SMD LED flexible strip - 60 LED/Meter * L 5000mm x W 10mm x H 5mm * Input Voltage: DC12V * 4.8W/Meter * Waterproof IP68 * Epoxy Resin Filled PVC Tube * Dimmable * Cool White: 390 Lumens/Meter	\$71.00
SMD3528 60LED/METER IP68 Light Strip		Product No: SLFLEXSTRIP-02W-D * 3528 SMD LED flexible strip - 60 LED/Meter * L 5000mm x W 10mm x H 5mm * Input Voltage: DC12V * 4.8W/Meter * Waterproof IP68 * Epoxy Resin Filled PVC Tube * Dimmable * Warm White: 360 Lumens/Meter	\$71.00
SMD5050 30LED/METER IP68 Light Strip		Product No: SLFLEXSTRIP-03C-D * 5050 SMD LED flexible strip - 30 LED/meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 7.2W/Meter * IP68 * Dimmable * Cool White: 585 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Epoxy Resin Filled PVC Tube	\$83.00
SMD5050 30LED/METER IP68 Light Strip		Product No: SLFLEXSTRIP-03W-D * 5050 SMD LED flexible strip - 30 LED/meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 7.2W/Meter * IP68 * Dimmable * Warm White: 540 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Epoxy Resin Filled PVC Tube	\$83.00

Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com







LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>SMD5050 RGB 30LED/METER IP68 Light Strip</p>		<p>Product No: SLFLEXSTRIP-03RGB-D * 5050 SMD LED flexible strip – 30 LED/meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 7.2W/Meter * IP68 * RGB: 60–120 Lumens/Meter * Epoxy Resin Filled PVC Tube</p>	<p style="text-align: center;">\$83.00</p>
<p>SMD5050 60LED/METER IP20 Light Strip</p>		<p>Product No: SLFLEXSTRIP-04C-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 11.8W/Meter * IP20 * Dimmable * Cool White: 900–1170 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Non Waterproof</p>	<p style="text-align: center;">\$114.00</p>
<p>SMD5050 60LED/METER IP20 Light Strip</p>		<p>Product No: SLFLEXSTRIP-04W-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 11.8W/Meter * IP20 * Dimmable * Warm White: 720–1080 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Non Waterproof</p>	<p style="text-align: center;">\$114.00</p>
<p>SMD5050 RGB 60LED/METER IP20 Light Strip</p>		<p>Product No: SLFLEXSTRIP-04RGB-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 11.8W/Meter * IP20 * RGB: 120–240 Lumens/Meter * Non Waterproof</p>	<p style="text-align: center;">\$114.00</p>
<p>SMD5050 60LED/METER IP68 Light Strip</p>		<p>Product No: SLFLEXSTRIP-05C-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 14.4W/Meter * IP68 * Dimmable * Cool White: 900–1170 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Epoxy Resin Filled PVC Tube</p>	<p style="text-align: center;">\$130.00</p>
<p>SMD5050 60LED/METER IP68 Light Strip</p>		<p>Product No: SLFLEXSTRIP-05W-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 14.4W/Meter * IP68 * Dimmable * Warm White: 720–1080 Lumens/Meter * Also available in Red, Yellow, Blue, Green * Epoxy Resin Filled PVC Tube</p>	<p style="text-align: center;">\$130.00</p>



Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com







LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>SMD5050 RGB 60LED/METER IP68 Light Strip</p>		<p>Product No: SLFLEXSTRIP-05RGB-D * 5050 SMD LED flexible strip – 60 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 14.4W/Meter * IP68 * RGB: 120–240 Lumens/Meter * Epoxy Resin Filled PVC Tube</p>	<p style="text-align: center;">\$130.00</p>
<p>SMD5050 30LED/METER Color Tracing Strip IP20</p>		<p>Product No: SLFLEXSTRIP-06RGB-D * 5050 SMD LED flexible strip – 30 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 7.2W/Meter * Non-Waterproof IP20 * DIGITAL Color Tracing RGB * Color Effect: single color, color gradual change, color transition</p>	<p style="text-align: center;">\$149.00</p>
<p>SMD5050 30LED/METER Color Tracing Strip IP67</p>		<p>Product No: SLFLEXSTRIP-07RGB-D * 5050 SMD LED flexible strip – 30 LED/Meter * 5 Meters (L 5000mm x W 10mm x D 2.5mm) * Input Voltage: DC12V * 7.2W/Meter * Waterproof IP67 * DIGITAL Color Tracing RGB * Color Effect: single color, color gradual change, color transition</p>	<p style="text-align: center;">\$149.00</p>
<p>Silicon Glue</p>		<p>Product No: SL-SG * Silicon Glue for Waterproof Flex LED Strips</p>	<p style="text-align: center;">\$3.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL50MC * IP50 DC Connector * Single Color</p>	<p style="text-align: center;">\$4.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL652BC-SC * Single Color Connector</p>	<p style="text-align: center;">\$4.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Flex Strip Accessories</p>		<p>Product No: SL652BC-RGB * RGB Connector</p>	<p>\$4.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL202WC-SC * Single Color Wire Connector</p>	<p>\$4.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL204WC-RGB * RGB Wire Connector</p>	<p>\$4.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL2WC-SC * Single Color Wire Connector</p>	<p>\$3.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL4WC-RGB * RGB Wire Connector</p>	<p>\$3.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL2WCA-SC * Single Color Connector</p>	<p>\$3.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Flex Strip Accessories</p>		<p>Product No: SL2WCB-SC * Single Color Connector</p>	<p style="text-align: center;">\$4.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL4WCA-RGB * RGB Connector</p>	<p style="text-align: center;">\$3.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SL4WCB-RGB * RGB Connector</p>	<p style="text-align: center;">\$3.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SLRA3528 * IP20 Right Angle Connector for 3528 Strips</p>	<p style="text-align: center;">\$5.00</p>
<p>Flex Strip Accessories</p>		<p>Product No: SLRA5050 * IP20 Right Angle Connector for 5050 Strips</p>	<p style="text-align: center;">\$5.00</p>
<p>RGB Strip Controller</p>		<p>Product No: SLRGB-CONTROLLER-01 * LED Strip RGB Controller * Wireless Remote * Power Supply 12-24V DC * FCC</p>	<p style="text-align: center;">\$66.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>RGB Strip PLAY Controller</p>		<p>Product No: SLRGB-CONTROLLER-02 * RGB LED Color Tracing Strip Multi-Function Controller * RF Wireless Remote * Power Supply 12-24V DC</p>	<p style="text-align: center;">\$348.00</p>
<p>RGB Strip PLAY Receptor</p>		<p>Product No: SLRGB-RECEPTOR * LED Strip RGB Receptor for use with SLRGB-CONTROLLER-02 and Color Tracing RGB Strips * RF Wireless Remote Receptor * Power Supply 12-24V DC</p>	<p style="text-align: center;">\$54.00</p>
<p>LED Strip Repeater</p>	<p style="text-align: center;">No Image Available</p>	<p>Product No: SLRGB-REPEATER * LED Strip RGB Repeater for using multiple strips * Wireless Remote * Power Supply 12-24V DC</p>	<p style="text-align: center;">\$57.00</p>
<p>RGB Strip Controller</p>		<p>Product No: SL-LLT100B * LED Strip RGB Controller * Remote Control * 120W Control Capacity of 15M (30 LED/M RGB Strips) * Aluminum Shell</p>	<p style="text-align: center;">\$41.00</p>
<p>RGB Strip Controller</p>		<p>Product No: SL-LLT300A * DMX Controller * 36 Colour Changing Modes * 150W (12V) * Control Capacity of 20M (30 LED/M RGB Strips)</p>	<p style="text-align: center;">\$120.00</p>
<p>RGB Strip Controller</p>		<p>Product No: SL-LLT300B * DMX Controller * 38 Colour Changing Modes * 300W (12V) * Control Capacity of 40M (30 LED/M RGB Strips)</p>	<p style="text-align: center;">\$228.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Digital RGB Strip Controller</p>		<p>Product No: SL-LLT100C * RF Remote Controller * Control Capacity of 10M (30 LED/M RGB Strips)</p>	<p style="text-align: right;">\$54.00</p>
<p>Digital RGB Strip Controller</p>		<p>Product No: SL-LLT203A * DMX Controller * Multi Function * Control Capacity of 25M (30 LED/M RGB Strips)</p>	<p style="text-align: right;">\$120.00</p>
<p>Digital RGB Strip Controller</p>		<p>Product No: SL-LLT203B * DMX Controller * Multi Function * Control Capacity of 100M (30 LED/M RGB Strips)</p>	<p style="text-align: right;">\$240.00</p>
<p>LED Strip Amplifier</p>		<p>Product No: SL-LLT390A * Amplifier for SL-LLT300A * 150W (12V)</p>	<p style="text-align: right;">\$25.00</p>
<p>LED Strip Amplifier</p>		<p>Product No: SL-LLT390B * Amplifier for SL-LLT300B * 300W (12V)</p>	<p style="text-align: right;">\$65.00</p>
<p>LED Strip Dimmer</p>		<p>Product No: SL-LLT400C * Dimmer for SINGLE COLOUR Strips * Knob Type * Output Voltage: 5V/6V/12V/24V Option * Output Current: <8A x 1 Channel</p>	<p style="text-align: right;">\$20.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>LED Strip Dimmer</p>		<p>Product No: SL-LLT400D * Dimmer for SINGLE COLOUR Strips * Touch Pad Type * Output Voltage: 5V/6V/12V/24V Option * Output Current: <8A x 1 Channel</p>	<p style="text-align: right;">\$24.00</p>
<p>LED Strip Dimmer</p>		<p>Product No: SL-LLT400E * Dimmer for SINGLE COLOUR Strips * Remote Type * Output Voltage: 5V/6V/12V/24V Option * Output Current: <8A x 1 Channel</p>	<p style="text-align: right;">\$28.00</p>
<p>Light Tube T5 2 Foot</p>		<p>Product No: SLT5-2FTW 5050 SMD LED Tube Length: 550 mm Power: 8 W Input Voltage: DC24V Lumens: 400-450 Available in Clear, Milky, Frosted CCT (K): WW 3000-3500K CE,RoHS</p>	<p style="text-align: right;">\$34.00</p>
<p>Light Tube T5 2 Foot</p>		<p>Product No: SLT5-2FTN 5050 SMD LED Tube Length: 550 mm Power: 8 W Input Voltage: DC24V Lumens: 400-450 Available in Clear, Milky, Frosted CCT (K): NW 4000-4500K CE,RoHS</p>	<p style="text-align: right;">\$34.00</p>
<p>Light Tube T5 2 Foot</p>		<p>Product No: SLT5-2FTC 5050 SMD LED Tube Length: 550 mm Power: 8 W Input Voltage: DC24V Lumens: 400-450 Available in Clear, Milky, Frosted CCT (K): CW 6000-6500K CE,RoHS</p>	<p style="text-align: right;">\$34.00</p>
<p>Light Tube T5 4 Foot</p>		<p>Product No: SLT5-4FTW 5050 SMD LED Tube Length: 1150 mm Power: 15W Input Voltage: DC24V Lumens: 700-750 Available in Clear, Milky, Frosted CCT (K): WW 3000-3500K CE,RoHS</p>	<p style="text-align: right;">\$65.00</p>

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Light Tube T5 4 Foot</p>		<p>Product No: SLT5-4FTN 5050 SMD LED Tube Length: 1150 mm Power: 15W Input Voltage: DC24V Lumens: 700-750 Available in Clear, Milky, Frosted CCT (K): NW 4000-4500K CE,RoHS</p>	<p style="text-align: center;">\$65.00</p>
<p>Light Tube T5 4 Foot</p>		<p>Product No: SLT5-4FTC 5050 SMD LED Tube Length: 1150 mm Power: 15W Input Voltage: DC24V Lumens: 700-750 Available in Clear, Milky, Frosted CCT (K): CW 6000-6500K CE,RoHS</p>	<p style="text-align: center;">\$65.00</p>
<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-02W 18 Watts – 288 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 18W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 1800 Available in Clear, Pinstripe, Frosted CCT (K): WW 2500-3500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$67.00</p>
<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-02N 18 Watts – 288 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 18W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 1800 Available in Clear, Pinstripe, Frosted CCT (K): NW 4000-5000K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$67.00</p>
<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-02C 18 Watts – 288 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 18W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 1800 Available in Clear, Pinstripe, Frosted CCT (K): CW 5500-6500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$67.00</p>
<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-03W 20 Watts – 360 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 20W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 2000 Available in Clear, Pinstripe, Frosted CCT (K): WW 2500-3500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$74.00</p>

Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-03N 20 Watts – 360 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 20W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 2000 Available in Clear, Pinstripe, Frosted CCT (K): NW 4000-5000K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$74.00</p>
<p>Light Tube T8 4 Foot</p>		<p>Product No: SLT8-4FT-03C 20 Watts – 360 SMD LEDs Dimensions: 1200 mm x 26 mm Power: 20W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 2000 Available in Clear, Pinstripe, Frosted CCT (K): CW 5500-6500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$74.00</p>
<p>Light Tube T8 8 Foot</p>		<p>Product No: SLT8-8FT-01W 35 Watts – 600 SMD LEDs Dimensions: 2400 mm x 26 mm Power: 35W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 3500 Available in Clear, Pinstripe, Frosted CCT (K): WW 2500-3500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$129.00</p>
<p>Light Tube T8 8 Foot</p>		<p>Product No: SLT8-8FT-01N 35 Watts – 600 SMD LEDs Dimensions: 2400 mm x 26 mm Power: 35W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 3500 Available in Clear, Pinstripe, Frosted CCT (K): NW 4000-5000K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$129.00</p>
<p>Light Tube T8 8 Foot</p>		<p>Product No: SLT8-8FT-01C 35 Watts – 600 SMD LEDs Dimensions: 2400 mm x 26 mm Power: 35W Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 3500 Available in Clear, Pinstripe, Frosted CCT (K): CW 5500-6500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$129.00</p>
<p>EXTERNAL DRIVER Light Tube T8 8 Foot</p>		<p>Product No: SLT8ED-4FT-02W 18 Watts – 300 SMD LEDs Dimensions: 1200 mm x 26 mm EXTERNAL DRIVER (Dimmable Option Available) Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 1750 Available in Clear, Pinstripe, Frosted CCT (K): WW 2800-3500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$73.00</p>

Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com

LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>EXTERNAL DRIVER Light Tube T8 8 Foot</p>		<p>Product No: SLT8ED-4FT-02N 18 Watts – 300 SMD LEDs Dimensions: 1200 mm x 26 mm EXTERNAL DRIVER (Dimmable Option Available) Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 1900 Available in Clear, Pinstripe, Frosted CCT (K): NW 4500-5500K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$73.00</p>
<p>EXTERNAL DRIVER Light Tube T8 8 Foot</p>		<p>Product No: SLT8ED-4FT-02C 18 Watts – 300 SMD LEDs Dimensions: 1200 mm x 26 mm EXTERNAL DRIVER (Dimmable Option Available) Input Voltage: 90-277VAC Working: DC 36-40V Lumens: 2050 Available in Clear, Pinstripe, Frosted CCT (K): WW 6000-7000K cUL,CE,RoHS 3 Year Warranty</p>	<p style="text-align: center;">\$73.00</p>
<p>Light Panel 1x1 Foot</p>		<p>Product No: SLFP-01 * 300mm x 300mm x 13mm (12" x 12" x 0.5") * Lumens: 800 * Input voltage::AC100-240V * Working voltage: 24V DC * Power : 14W * CCT (K): WW-3000K, NW-4500K, CW-6000K * Includes CE, RoHS, UL Power Supply</p>	<p style="text-align: center;">\$119.00</p>
<p>Light Panel 4x2 Foot</p>		<p>Product No: SLFP-02C * 1200mm x 600mm x 14mm (48" x 24" x 0.5") * 78 Watt * Luminous Flux: 7900 lm * AC85V-264V to DC24V * 684 PCS 3014 SMD LED * Neutral White 5000K-5500K</p>	<p style="text-align: center;">\$372.00</p>
<p>Light Panel 2x2 Foot</p>		<p>Product No: SLFP-03C * 600mm x 600mm x 14mm (24" x 24" x 0.5") * 48 Watt * Luminous Flux: 3500 lm * AC85V-264V to DC24V * 228 PCS 5050 SMD LED * Neutral White 5000K-5500K</p>	<p style="text-align: center;">\$278.00</p>
<p>Light Panel 4x1 Foot</p>		<p>Product No: SLFP-04C * 1197mm x 297mm x 14mm (48" x 12" x 0.5") * 48 Watt * Luminous Flux: 4200 lm * AC85V-264V to DC24V * 234 PCS 5050 SMD LED * Neutral White 5000K-5500K</p>	<p style="text-align: center;">\$278.00</p>







LED Flexible Strips, LED Tubes, LED Panels, RGB Controllers, Accessories

<p>Panel UL Driver</p>		<p>Product No: SLPANELPS * UL/cUL Driver for All Panel Lights</p>	<p style="text-align: center;">\$46.00</p>
<p>SL-PR6161C IC TYPE PANEL LIGHT</p>		<p>Harvatek Chip with Driver & Enclosure 55 Watts Grid Reflector CCT: 3500K Lumens: 2500 Beam Angles Available: 80°/110° CRI > 80 610x610x115mm</p>	<p style="text-align: center;">\$369.00</p>
<p>SL-PR6161W IC TYPE PANEL LIGHT</p>		<p>Harvatek Chip with Driver & Enclosure 55 Watts Grid Reflector CCT: 6500K Lumens: 3000 Beam Angles Available: 80°/110° CRI > 70 610x610x115mm</p>	<p style="text-align: center;">\$369.00</p>
<p>SL-PC5555C SURFACE MOUNTED PANEL LIGHT</p>		<p>Harvatek Chip with Driver & Enclosure 60 Watts CCT: 3000K Lumens: 3000 Beam Angles Available: 120° CRI > 80 4 x LED Panel Design SURFACE Mount</p>	<p style="text-align: center;">\$449.00</p>
<p>SL-PC5555C SURFACE MOUNTED PANEL LIGHT</p>		<p>Harvatek Chip with Driver & Enclosure 60 Watts CCT: 5000K Lumens: 4000 Beam Angles Available: 120° CRI > 75 4 x LED Panel Design SURFACE Mount</p>	<p style="text-align: center;">\$449.00</p>







Distributed by: Eco-Smart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com

LED Rigid Light Bars, Accessories

TYPE	PICTURE	KEY SPECIFICATIONS	PRICE
Light Bar		Product No: SLRL-01W L 250mm x W 12mm x D 7mm 3W/Meter 135 Lumens DC 12V Quick Connect – Snap together segments IP65 SMD5050 – 9 LED Warm White	\$14.00
Light Bar		Product No: SLRL-01C L 250mm x W 12mm x D 7mm 3W/Meter 190 Lumens DC 12V Quick Connect – Snap together segments IP65 SMD5050 – 9 LED Cool White	\$14.00
Light Bar		Product No: SLRL-01RGB L 250mm x W 12mm x D 7mm 3W/Meter 9–45 Lumens DC 12V Quick Connect – Snap together segments IP65 SMD5050 – 9 LED RGB	\$14.00
Light Bar Accessories		Product No: SL654CC6 * Bar to Power connector for SLRL-01 * 10 cm	\$4.00
Light Bar Accessories		Product No: SL-BBC001 * Bar to Bar connector for SLRL-01 * Wire Length 100mm	\$4.00
Light Bar Accessories		Product No: SL-BBS001-2WAY * 2 Way Bar to Bar Splitter for SLRL-01 * Wire Length 100mm	\$4.00

LED Rigid Light Bars, Accessories

<p>Light Bar Accessories</p>		<p>Product No: SL-BBS001-4WAY * 4 Way Bar to Bar Splitter for SLRL-01 * Wire Length 100mm</p>	<p style="text-align: center;">\$5.00</p>
<p>Light Bar 30 cm</p>		<p>Product No: SLLB-01W * 30cm * Non-waterproof * SMD5050 LED * Warm white * CE,RoHS,UL</p>	<p style="text-align: center;">\$20.00</p>
<p>Light Bar 30 cm</p>		<p>Product No: SLLB-01C * 30cm * Non-waterproof * SMD5050 LED * Cool white * CE,RoHS,UL</p>	<p style="text-align: center;">\$20.00</p>
<p>Light Bar 60 cm</p>		<p>Product No: SLLB-02W * 60cm * Non-waterproof * SMD5050 LED * Warm white * CE,RoHS,UL</p>	<p style="text-align: center;">\$33.00</p>
<p>Light Bar 60 cm</p>		<p>Product No: SLLB-02C * 60cm * Non-waterproof * SMD5050 LED * Cool white * CE,RoHS,UL</p>	<p style="text-align: center;">\$33.00</p>
<p>Light Bar 100 cm</p>		<p>Product No: SLLB-03W * 100cm * Non-waterproof * SMD5050 LED * Warm white * CE,RoHS,UL</p>	<p style="text-align: center;">\$53.00</p>





LED Rigid Light Bars, Accessories

<p>Light Bar 100 cm</p>		<p>Product No: SLLB-03C * 100cm * Non-waterproof * SMD5050 LED * Cool white * CE,RoHS,UL</p>	<p style="text-align: center;">\$53.00</p>
<p>Stent Light</p>		<p>Product No: SLST-N * 585mm x 30mm * 7 Watt * AC 100-240V with built-in switch * 5050 SMD LED * Natural White - 4100K</p>	<p style="text-align: center;">\$61.00</p>
<p>Rigid Light Bar 2 Foot</p>		<p>Product No: SLRB-01W * 570mm x 28mm * 12 Watt * DC12V * 3528 SMD LED * Warm White - 4100K * CE,RoHS,UL LED Driver</p>	<p style="text-align: center;">\$77.00</p>
<p>Rigid Light Bar 2 Foot</p>		<p>Product No: SLRB-01C * 570mm x 28mm * 12 Watt * DC12V * 3528 SMD LED * Cool White - 6400K * CE,RoHS,UL LED Driver</p>	<p style="text-align: center;">\$77.00</p>
<p>Connector</p>		<p>Product No: SL-FJTBB21 * 3 inch flexible Bar to Bar connector * For SLLB Series LED rigid light bars</p>	<p style="text-align: center;">\$5.00</p>
<p>Connector</p>		<p>Product No: SL-FJTDC21 * 14 inches female power connector * For SLLB Series LED rigid light bars</p>	<p style="text-align: center;">\$5.00</p>

LED Rigid Light Bars, Accessories

<p style="text-align: center;">12 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-12W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 12W, 1 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$18.00</p>
<p style="text-align: center;">24 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-24W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 24W, 2 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$21.00</p>
<p style="text-align: center;">36 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-36W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 36W, 3 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$26.00</p>
<p style="text-align: center;">48 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-48W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 48W, 4 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$30.00</p>
<p style="text-align: center;">60 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-60W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 60W, 5 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$33.00</p>
<p style="text-align: center;">90 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-90W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 90W, 7.5 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$53.00</p>

LED Rigid Light Bars, Accessories

<p style="text-align: center;">120 WATT AC Adapter</p>		<p>Product No: SL12VADAPTER-120W AC Adapter for Light Bars and Strips With Power Cord Non-Waterproof Input AC100-240V 50/60Hz Output DC12V Max 120W, 10 Amp UL/cUL, CE, RoHS</p>	<p style="text-align: center;">\$67.00</p>
<p style="text-align: center;">Constant Current Driver</p>		<p>Product No: SLCCD3512-3W * Constant Current Driver WITHOUT Power Cord * Input AC100-240V 50/60Hz * Output DC12V Max 3W 350mA * LED's to Driver: (1-3) x 1W LEDs * UL/cUL, TUV/RoHS</p>	<p style="text-align: center;">\$12.00</p>
<p style="text-align: center;">Constant Current Driver</p>		<p>Product No: SLCCD7012-6W * Constant Current Driver * Input AC100-240V 50/60Hz * Output DC12V Max 6W 700mA * LED's to Driver: (1-2) x 3W LEDs * UL/cUL, TUV/RoHS</p>	<p style="text-align: center;">\$12.00</p>
<p style="text-align: center;">Constant Current Driver</p>		<p>Product No: SLCCD3512-8W * Constant Current Driver with Power Cord * Input AC100-240V 50/60Hz * Output DC12V, Max 8W, 350mA * LED's to Driver: (1-8) x 1W LEDs * UL/cUL, TUV/RoHS</p>	<p style="text-align: center;">\$14.00</p>

LED Flood Lights, Solar LED Flood Lights

TYPE	PICTURE	KEY SPECIFICATIONS	PRICE
LED RGB Flood		Product No: SLFL-01 Power: 1W x 36 Pieces (R:12/G:12/B:12) Voltage: DC24V Colors: WHITE, RGB (R/G/B/Y/W/RGB) Beam Angle: 45 Degrees IP65 Control: DMX512 Material: AL6063 + Tempered Glass Length:310mm, Width 155mm, Height 112mm	\$290.00
LED Flood		Product No: SLFL-02 Power: 1W x 48 Pieces Voltage: 100-240V 50/60Hz Colors: White, Blue, Green, Yellow, Red, RGB Beam Angle: 45 Degrees IP65 Control: DMX512 Material: AL6063 + Tempered Glass Length:640mm, Width 326mm, Height 210mm	Solid Color \$357.00 RGB \$372.00

Distributed by: Eco-\$mart, Inc.

Phone: (888)329-2705 Fax: (941)377-9460 info@eco-smart.com