

Eco-\$mart, Inc. 4411 Bee Ridge Rd. #344 Sarasota, FL 34233 888-329-2705 ph / 941-377-9460 fx www.eco-smart.com.com

METLUND D'MAND Recircualtion Systems

A complete system to convert standard plumbed homes into a **D'MAND** Recirculation System using the existing plumbing.

The *D'MAND System* also works on dedicated return lines with tank or TANKLESS water heaters (call for more information). Includes electronic circuit board with thermo sensor, bronze high performance potable water circulating pump with built-in Integral Flow Valve and momentary contact button.

Product Price		rice		
S-50T	\$ 2	266.67	1/2" mip, button, for use on dedicated return lines	This System is designed for hot water runs up to 50 feet.
S-50T-FL	\$ 2	286.67	1/2" mip, button, 2 3/4 M/F 18" flexlines	Includes electronic circuit board w/ thermo sensor.
S-50T-PF	\$ 3	328.00	1/2" mip, button, 2 custom brass T's, 2 3/4 M/F 18" flexlines & 2 adptrs.	The flow rating is 8 gpm/12 feet of head.
S-50T-PF-R	\$ 3	356.00	1/2" mip, button, 2 custom brass T's, 2 3/4 M/F 18" flexlines, 2 adptrs.	Internal Control Valve (IFC), no check valve required
			& 1 receiver and 1 wireless transmitter.	(not recommended for gas tankless water heaters)
S-70T	\$ 3	322.67	1/2" mip, button, for use on dedicated return lines	This System is designed for hot water runs up to 100 feet.
S-70T-R	\$ 3	353.33	1/2" mip, button, 1 receiver & 1 wireless transmitter (**)	Includes electronic circuit board w/ thermo sensor.
S-70T-FL	\$ 3	357.33	1/2" mip, button, 2 3/4 M/F 18" flexlines & 2 adptrs.	The flow rating is 14 gpm/16 feet of head.
S-70T-PF	\$ 3	394.67	1/2" mip, button, 2 custom brass T's, 2 3/4 M/F 18" flexlines & 2 adptrs.	Internal Control Valve (IFC), no check valve required
S-70T-PF-R	\$ 4	126.67	1/2" mip, button, 2 custom brass T's, 2 3/4 M/F 18" flexlines, 2 adptrs.	(check specifications for tankless water heaters)
			& 1 receiver and 1 wireless transmitter.	
S-02T	\$ 4	173.33	3/4" fip, button, for use on dedicated return lines	This System is designed for hot water runs over 100 feet.
S-02T-R	\$ 4	198.67	3/4" fip, button, 1 receiver & 1 wireless transmitter (**)	Includes electronic circuit board w/ thermo sensor.
S-02T-FL	\$ 5	550.67	3/4" fip, button, 2 3/4 M/F 18" flexlines	The flow rating is 26 gpm/32 feet of head.
S-02T-PF	\$ 5	28.00	3/4" fip, button, 2 custom brass T's & 2 18" M/F flexlines	Internal Control Valve (IFC), no check valve required
S-02T-PF-R	\$ 5	553.33	3/4" fip, button, 2 custom brass T's, 2 18" M/F flexlines &	(check specifications for tankless water heaters)
			1 receiver and 1 wireless transmitter	
Accessories	Pr	rice		Terms:
RT-954	\$	39.93	Wireless remote package (1 receiver & 1 wireless transmitter)	Prepaid by Check, Visa, Master or AMX
T-954	\$	21.00	Individual wireless transmitter (5 volt)	No returns after 30 days
B-922G	\$	3.53	Button/round whitecenter with brass ring - momentary contact button	
B-706S	\$	5.00	Button/round whitecenter with silver ring - momentary contact button	
V-102	\$	63.00	Hardwire Motion Sensor (12 volt)	NOTE:
VRS-1101	\$ 2	224.00	Wireless Motion Sensor pkg. /1 receiver & 1 motion sensor (12 volt)	 Momentary contact button used with all pumps.
VS-1101	\$ 1	33.00	Individual wireless motion sensor (12 volt)	(**) for use on dedicated return lines
Dant	Part Price			"mip" = male inlet pipe threaded for flexlines to mate
Part		10.47	Mounting Bracket for S-50T and S-70T	If in II formall in latering
MBS-606	\$	10.47	Modificing Bracket for 6 cort and 6 701	"fip" = femail inlet pipe
		14.13	Mounting Bracket for S-02T	np = remail inlet pipe
MBS-606	\$		Mounting Bracket for S-02T Custom Brass "T" Compression Fittings (for 1/2" copper pipe)	rip = remaii iniet pipe
MBS-606 MBL-606	\$	14.13	Mounting Bracket for S-02T	iip = remaii iniet pipe
MBS-606 MBL-606 Brass T's pr.	\$ \$ \$	14.13 28.00	Mounting Bracket for S-02T Custom Brass "T" Compression Fittings (for 1/2" copper pipe)	iip = iemaii iniet pipe
MBS-606 MBL-606 Brass T's pr. SOVN-606	\$ \$ \$ \$	14.13 28.00 15.20	Mounting Bracket for S-02T Custom Brass "T" Compression Fittings (for 1/2" copper pipe) 2 3/4" fip shut off valves with 2 3/4" nipples (for use w/ S-50T & S-70T)	iip = remaii iniet pipe