

All-in-One Solar LED Street Light - Wholesale Prices

Validity of Offer: 1 Month | Sample's Delivery Time :Normallyly within 7 Days After your payment arrived

**3 YEAR
WARRANTY**



Spec.

Model No.	SLT-PVLD10
Nominal Power	10W
LED Number	7 units
LED Maintain Flux	1100 lumens
Light Type	1S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 16.80W/18V
Battery Spec.	9AH/12V
Constant Working at Full Power:	8 hours
Working at at Energy-saving Mode(25%):	≥40 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	3~4m
Installation Distance	12m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$232.40
101-500 Units	\$223.40

Dimension /Weight Info.

Fixture Info.	782 x301 x88 mm, 6.5kgs
Packing Type	1unit /ctn.
Packing Info.	825 x360 x145 mm, 8.1 kg

**3 YEAR
WARRANTY**



Spec.

Model No.	SLT-PVLD15
Nominal Power	15W
LED Number	7 units
LED Maintain Flux	1650 lumens
Light Type	1S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 16.80W/18V
Battery Spec.	9AH/12V
Constant Working at Full Power:	7 hours
Working at at Energy-saving Mode(25%):	≥35 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	3~4m
Installation Distance	15m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$276.40
101-500 Units	\$258.00

Dimension /Weight Info.

Fixture Info.	782 x301 x88 mm, 6.5kgs
Packing Type	1unit /ctn.
Packing Info.	825 x360 x145 mm, 8.1 kg

**3 YEAR
WARRANTY**



Dimension /Weight Info.

Fixture Info. 969 x301 x88 mm, 7.9kgs
 Packing Type 1unit /ctn.
 Packing Info. 1010 x360 x145 mm, 12.00 kg

Spec.

Model No.	SLT-PVLD20
Nominal Power	20W
LED Number	10 units
LED Maintain Flux	2200 lumens
Light Type	1S, 2S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 37.80W/18V
Battery Spec.	16.5AH/12V
Constant Working at Full Power:	7 hours
Working at at Energy-saving Mode(25%):	≥35 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	4~5m
Installation Distance	18m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$366.40
101-500 Units	\$357.60

**3 YEAR
WARRANTY**



Dimension /Weight Info.

Fixture Info. 1155 x363 x88 mm, 11.20kgs
 Packing Type 1unit /ctn.
 Packing Info. 1200 x420 x145 mm, 14.00 kg

Spec.

Model No.	SLT-PVLD30
Nominal Power	30W
LED Number	15 units
LED Maintain Flux	3300 lumens
Light Type	1S, 2S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 50.40W/18V
Battery Spec.	24AH/12V
Constant Working at Full Power:	7 hours
Working at at Energy-saving Mode(25%):	≥35 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	5~6m
Installation Distance	20m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$447.00
101-500 Units	\$438.00



Spec.

Model No.	SLT-PVLD40
Nominal Power	40W
LED Number	20 units
LED Maintain Flux	4400 lumens
Light Type	1S, 2S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 73.50W/18V
Battery Spec.	33AH/12V
Constant Working at Full Power:	7 hours
Working at at Energy-saving Mode(25%):	≥35 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	3~4m
Installation Distance	12m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$558.60
101-500 Units	\$549.60

Dimension /Weight Info.

Fixture Info.	1289 x447 x88 mm, 15.00kgs
Packing Type	1unit /ctn.
Packing Info.	1330 x505 x145 mm, 20.00 kg

Spec.

Model No.	SLT-PVLD50
Nominal Power	50W
LED Number	20 units
LED Maintain Flux	5500 lumens
Light Type	1S, 2S
CCT	3000K/ 4000K/ 5000K/ 6000K
Solar Panel Spec.	Monocrystal 73.50W/18V
Battery Spec.	40AH/12V
Constant Working at Full Power:	7 hours
Working at at Energy-saving Mode(25%):	≥35 Hours
Charge Time	Max power 5~6 Hours
Switch Lights Sense Threshold:	on ≤10 LXS, off ≥15 LXS
Installation Height	7~8m
Installation Distance	30m
Lamp Pole Diameter	40~60mm

FOB Shanghai or Ningbo, China

1-100 Units	\$634.60
101-500 Units	\$625.60

Dimension /Weight Info.

Fixture Info.	1289 x447 x88 mm, 15.70kgs
Packing Type	1unit /ctn.
Packing Info.	1330 x505 x145 mm, 20.70 kg



CE Conformity
Certified by TUV SUD



RoHS Compliant
Tested by TUV SUD



ISO 9001 & 14001



Highest Quality



Optimal Performance



Eco-Friendly &
Energy-Saving